

FT-2980R

144MHz 80W FM Single Band Mobile Transceiver

Heavy Duty FM Single Band Mobile

Radio Features:

- Massive Heatsink guarantees 80 Watts of RF Power with No Cooling Fan Needed
(Four selectable power output levels are provided: 80/30/10/5 Watts)
- Loud 3 Watts of Audio Output for noisy environments
- Large 6 Digit Backlit LCD ensure excellent visibility
- Excellent Receiver Performance
- Alpha-Numeric Channel Display
- 200 Memory Channels for serious users
- CTCSS and DCS Encode/Decode Built in
- Versatile Scanning Capability
- WX Channels with "Severe Weather" Alert
- Smart Search Operation
- DTMF Direct Access Microphone Included
- Wide/Narrow Deviation Selection
- RF-Squelch
- Interactive Programming Menu
- Supply Voltage Display
- 4-level Display Dimmer
- Dual Watch



FT-2980R

Supplied Accessories:

DTMF Microphone(MH-48A6JA)
Mobile Mounting Bracket(MMB-83)
DC Power Cord w/Fuse
Spare Fuse (25 A)
Standing Foot
Operating Manual
Warranty Card

Specifications:

Frequency Ranges: RX 136 - 174 MHz

TX 144 - 148 MHz

Circuit Type: Double-Conversion Superheterodyne
Modulation Type: F3E(FM), F2D(PACKET)
Output Power: 80 W/30W/10W/5W
Memory Channels: 200
Case Size(W x H x D): 6.3" x 2.0" x 7.3" (w/o Knobs)
Weight: 4.2 lbs
Qty in Master Carton: 5
Warranty: 3 Years